







- **Designed to hold up to (4) 12 gauge USE-2 or (4) 10 gauge PV-1000V solar wires.** Also for use with other types of cables from .20" (5,1 mm) to .30" (7,6 mm) in diameter.
- Reinforced spine for better rigidity with maximum cables.
- Contoured finger design for secure cable gripping from minimum to maximum cable diameter.
- Designed to provide a better method for PV module wire management and may be used whenever multiple cable management is needed.
- Smooth clip edges prevent damage to cable insulation.
- SunRunner 4 Cable Clip is designed to accommodate thicker racking systems up to .250" (6,4 mm) thick.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant.

HEYClip™ SunRunner® 4 Cable Clip



PANEL THICKNESS CLAMPING RANGE				WIRE DIA. RANGE Maximum (4) Wires	PART NO.	DESCRIPTION	FOOTPRINT A x B		OVERALL HEIGHT C	
Minimum in.	Maximum mm.	Minimum in.	Maximum mm.				in.	mm.	in.	mm.
Double-Compression Design for panels up to .250" (6,4 mm) thick										
.13	3,2	.25	6,4	.20" (5,1 mm)- .30" (7,6 mm) each cable	S6400	SunRunner 4 100 Pack	1.34 x .50	34,0 x 12,7	.36	9,1
					S6440	SunRunner 4 Bulk				



SunRunner® 4™



SunRunner® 90°



SunRunner® 90-2

HEYClip™ SunRunner® 90° Cable Clips


Double-Compression, Right Angle Design

PANEL THICKNESS CLAMPING RANGE				WIRE DIA. RANGE Maximum (1) Wire	PART NO.	DESCRIPTION	FOOTPRINT A x B		OVERALL HEIGHT C	
Minimum in.	Maximum mm.	Minimum in.	Maximum mm.				in.	mm.	in.	mm.
Single Wire Clip										
.06	1,4	.13	3,2	.20" (5,1 mm)- .30" (7,6 mm) each cable	S6406	SunRunner 90° 100 Pack	.65 x .78	16,5 x 19,8	.39	9,9
					S6446	SunRunner 90° Bulk				

Double Wire Clip										
.06	1,4	.13	3,2	.20" (5,1 mm)- .30" (7,6 mm) each cable	S6436	SunRunner 90-2 100 Pack	.65 x .98	16,5 x 24,9	.39	9,9
					S6476	SunRunner 90-2 Bulk				

NEW PRODUCTS

- **SunRunner 90° Cable Clip is designed to mount at a 90° angle to the original SunRunner®.**
- The SunRunner 90° will accommodate a single cable from .20" (5,1 mm) to .30" (7,6 mm); SunRunner 90-2 will accommodate (2) of these cables.
- SunRunner 90° is designed for use with PV modules mounted in the "landscape" mode. PV modules with shorter than normal junction box cables cannot be dressed out to the sides of the module. The SunRunner 90° will allow the junction box cables to be run to the adjacent modules across the short side of the PV module frame.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- DFARS Compliant.



Material SunRunner 4 – .020" thick heat treated 410 stainless steel
SunRunner 90° – .025" thick 304 stainless steel
Certifications Certified by UL for Compliance with both Canadian and US Requirements under File E54523 (SunRunner 90 only)